

PARTNUMBER: 22-0961

OVAL SPEAKER 41 X 71 MM 4Ω 2W



### SPECIFICATION

Item	Standard	Test Condition	
VOICE COIL IMP.	4 Ω ± 15%	AT 400 HZ 1.0V	
VOICE COIL IMP.	3.6 Ω ± 15%	AT 400 HZ 1.0V	
BUZZES & RATTLES	MUST BE NORMAL	SINE WAVE 2.8 V/150~1500HZ	
RESONANT FREQ	330HZ ± 20%		
OUTPUT S-P-L	MEAN VALUE AT 82.0±2DB 0.6 , 0.8 , 1.0 , 1.2 KHZ	AT 1W AXIS CALCULATED FROM 1M MEASUREMENT.	
FREQ. RESPONSE	220 – 2000HZ OUTPUT SPL -10DB		
RATED POWER INPUT	2 W	SINE WAVE PROGRAM SIGNAL	
MAX. POWER INPUT	4 W		
TEMPERATURE RANGE	-25 ~ 70°C		
DISTORTION	5% LESS MAX.	RATED POWER INPUT	
LOAD TEST	AFTER TEST MEET ITEM 2 & 3	PINK NOISE 2 W 24 HOURS	
HEAT TEST	AFTER TEST MEET ITEM 2 & 3	70±2°C 20~25% R.H. 24 HOURS 40±2°C 90~95% R.H. 24 HOURS	
FLUX DENSITY	GAUSS		
VOICE COIL		CONE PAPER	
BOBBIN MATERIAL	PAPER	DIAPHRAGM MATERIAL	PAPER
WIRE MATERIAL	LOCK	EDGE MATERIAL	FORM
VOICE COIL I.D. (MIN)	φ 13 MM	TOP PLATE THICKNESS	2MM
MAGNET		FRAME	
WEIGHT	MAIN: GR φ 12.5 * 3 TMM	MATERIAL	FE
SIZE		FINISH	BLACK PAINTING
MATERIAL	ND-FE-B	DUST CAP MATERIAL	PAPER
CONNECTIONS	4.8 X 0.5MM (+)	2.8 X 0.5MM (-)	
QUALITY INSPECTION LEVEL		II AQL (0.65)MA (2.5)MI	

